

SayHi™

ES  NE

ES6xx Series IP Phone

ES610
ES620
IP Phone



www.escene.hk

SayHi ES6xx represents the next-generation 8-line SIP phone that feature large HD graphic LCD display, 4 dynamic context-sensitive soft keys, dual 10/100Mbps auto-sensing Ethernet ports with integrated PoE. The ES6xx series offer excellent voice clarity, comprehensive telephony features, automated provisioning, security protection for privacy. It is a powerful IP telephone for advanced enterprise users.

ES6xx series include two kinds of products with different screen:ES610(high-definition graphic screen),ES620(high-definition color screen).

Key Features:

- 480x272 HD Color LCD(ES620)
- 480x272 graphic LCD(ES610)
- Customizable Screen
- 8 VoIP accounts
- VoIP+PSTN
- Adjustable bracket
- HD Voice: HD Codec
- BLF, XML Phonebook
- Headset,PoE,2xRJ45
- 6 Expansion Modules



Item	ES610	ES620
Screen	High-definition Graphic LCD with Background light 480*272 pixel	High-definition color LCD with Background light
Line	8	
Function Keys	4 soft keys, 8 Line keys 6 Navigation keys(Arrow button, OK button, C button) Volume adjust, Hands-free, Mute, Headset, Message, Menu Directory, Service, Hold, Redial, Conference, Transfer	
VoIP Protocol	SIP 2.0	
Network Protocol	HTTP, BOOTP, FTP, TFTP, IEEE 802.1Q, IEEE 802.1X	
Codec	G.723.1, G.729 A/B, G.711 A/U, G.722	
QoS	TOS, Jiffer Buffer, VAD, CNG, G.168 (32ms)	
Network	2×RJ45 10/100M Ethernet Interfaces (LAN/PC) IP Assignment: static IP or DHCP DNS Client	
Speech	Handle, Headset and Hands-free mode available Support call centre headsets and PC headsets Separated 8 Level Volume Adjustment	
Call Processing	Line Status Indicator Multi Account Call Waiting, Call Queuing, Line Switching Call Forward, Call Transfer, Call Holding, Call Pickup, Callback One Key Dial, Redial Phone directory speed dial, call record direct dial 3-way conference DnD, Blacklist Voice mail, Voice Prompt, Voice Message BLF	
Expansion Interface	EXT: ESM32 programmable Key module SOR: FXS, FXO, Record USB	
Application	Public phone directory Private phone directory PnP(Plug&Play) Photograph album XML Used as intellectual terminals	
Security	Login the website by password Signaling encryption Media encryption	
Management	Upgrade: HTTP/TFTP/PnP auto-provision Configurations: Phone/Web/auto-provision Debug: Telnet/Phone/Web	
Power Supply	Power adapter: AC100~240V input and DC 12V/1A output PoE(IEEE 802.af)	
Specifications	Storage Temperature: 0°C ~ 60°C Operating Humidity: 10%~90% Size: 254mm*205mm*87mm Net weight: 0.9kg	
Package Features	Qty/CTN:10 PCS N.W/CTN: 9kg G.W/CTN: 11kg Measurement: 0.081CBM Carton Meas: 525mm*430mm*360mm	
Certifications	CE	

Escene Communication Technology Co., Ltd

www.escene.hk

Headquarter (Guangzhou):
Add: No. 209 Yuehe Building, No.54
Huacui Street, Tianhe Industrial Park,
Guangzhou, China.
Tel:(+86)20-85543101 Fax: (+86)20-85540528

Beijing Office:
Add: Room 2804, No.115 Datunli
Subdistrict, Asian Games Village,
Chaoyang District, Beijing, China.
Tel:(+86)10-84805575

Shanghai Office:
Add: Room 1308, Baocheng
Building, No.269 Meidong Road,
Shanghai, China.
Tel:(+86)21-54936336

